

18V BRUSHLESS IMPACT WRENCH



Product description

HT2E225-0ID : Efficient device that ensuring ease and speed of work for quickly screwing in and out, as well as loosening and tightening, even long screws in wood and sheet metal. Unscrewing and tightening large screws and nuts in metal and wooden structures. Excellent for carpentry workshops and companies creating framework structures from metal and wood. Created for works, which cannot be easily handled with a drill-driver. Quick-change hexagonal holder, 1/4" (inch) HEX type, facilitates quick replacement of bits and their secure fixation during work. High torque of 200 Nm enables working with combined components, requiring high power. Impact mechanism increases working efficiency at low handle reaction. Robust anvil in the impact mechanism thanks to excellent materials used to manufacture it. Three torque settings enable adapting the tool to different tasks, preventing damage to screws, bolts and nuts. Soft handle enables more reassuring grip of the power tool and dampens vibrations during operation. Changing the rotation of the power tool in both directions enables efficient screwing in and unscrewing. Smooth adjustment of rotational speed in the power switch provides greater flexibility and work control. The built-in, powerful LED perfectly illuminates the workplace even in the darkest areas, eliminating shadows on terminals and connectors. Brushless motor with innovative construction, thanks to the elimination of brush friction and special magnets offers greater power, longer operation time and lifespan of the device. Advanced electronic circuits continuously regulate the motor operation, optimizing its power according to the performed activity, which translates into efficiency and maximization of the battery operation time. Durable, metallic housing of the gearbox excellently dissipates heat, making the device more efficient and robust. Gearbox made of metal enhances the wear resistance and ensures precision of the mechanism. Thermal safety device protects the tool against overheating during operation. Rubber bumpers protect the device against mechanical damage. OneAccuSystem 18 V enables using the selected battery in a wide and diverse range of power tools for the most heavy-duty work. HT2E242-C60: An efficient charger that will charge a 2 Ah battery in just approx. 30 min. An advanced electronic module monitors battery voltage and temperature to maximise the efficiency of the charging process and ensure long battery life. Overheating protection extends the use life and battery life. Current short circuit protection improves the safety of the charging process. Monitoring the charge level of the cells extends their life. Indicators show the battery status and inform about the charging process. HT2E240-A40: Perfectly balanced in terms of low weight, small size, and capacity, a rechargeable battery for many different tools offered by the brand. An advanced electronic module monitors battery operation to maximize performance, operating time, increase durability and safety. Cell overheating protection, extending their operating time and enhancing their durability. Short circuit protection increases safety of work and storage of the rechargeable battery. Charging level control extends the life cycle of the cells. Cells made in the latest lithium-ion (Li-Ion) technology ensure high energy efficiency, robustness and reliability. Housing protected with rubber bumpers protects against mechanical damage. Cell protection against moisture. Operation possible from - 18 °C of external temperature, extends the scale of tool use. Charging level shows the available energy.

Characteristics

HT2E225-0ID:

- Maximum torque – 200 Nm.

- Rotational speed: 0-900/0-2000/0-2800 Min.
- Torque in gears: 85/ 150 200 Nm.
- Impact Rate: 0-3100 IPM;
- 3 settings of rotational speed / torque;
- Smooth speed adjustment in the power switch.
- Soft, anti-slip handle.
- Right and left rotation direction switch.
- Metal gearbox housing.
- LED light.
- Weight – 1.17 kg.
- Metal gearbox housing.
- Metal gearbox mechanism.
- Brushless motor.
- Device overheat protection.
- 3 years warranty after registering the tool.
- EAN code – 5902801442834.
- 3 years warranty after registering the tool.
- OneAccuSystem.
- Voltage – 18 V.
- The rechargeable battery to be purchased separately.

HT2E242-C60:

- Voltage 18 V.
- Current 4A.
- Weight 0.56kg.
- Protections - overheating, overcharging, short circuit.
- Charging process indicator.
- Charging time 80 % of a 2 A battery - 30 min.
- Charging time 80 % of a 4 A battery - 60 min.
- Charging time 80 % of a 6 A battery - 90 min.

HT2E240-A40:

- Li-Ion technology.
- Voltage – 18 V.
- Capacity – 4.0 Ah.
- Weight – 0.67 kg.
- Protection against overheating, overcharging, short circuit.
- Charging level.
- EAN code – 5902801489785.

Technical data

			
HT2E255-B14ID	5902801488481	1	4

Höbert Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland

Producent/ Manufacturer/ Hersteller/ Произведено для:
PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków,
Polska/ Poland/ Polen/ Польша

Importer/ Импортёр:

HR GTV Croatia d.o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska
Distributor:

ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón
308, 46021 Valencia, Spain

CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince
879, 720 00 Ostrava Hrabová

07.2024