

PRODUCT INFORMATION SHEET

Floodlight with base 5400 lm



Product description

The floodlight, thanks to SMD LEDs, allows effective lighting of the workplace. The adjustment of arms makes it possible to control the angle of incidence of light, improving work comfort. Thanks to its water and dust resistance (IP54), the floodlight can be used wherever precise illumination of an object is required. Resistance to impact energy of 5 J (IK08) and temperature exposure guarantee lighting in particularly difficult conditions of renovation or construction works.

Characteristics

Luminous flux - 5400 lm;
 Dust and water resistance - IP54;
 Impact protection class - IK08;
 LED type - SMD2835 36+2x15pcs;
 Cable length - 2,5 m;
 Operating temperature - from -25 to +45oC;
 Operating voltage - 100 – 240 V ~ 50/60 Hz;
 Colour temperature - 5000 K;

Technical data

			
HT1E456	5902801620645	1	4

Högert Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland
 Producent/ Manufacturer/ Hersteller/ Произведено для:
 PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków, Polska/ Poland/ Polen/ Польша
 Importer/ Импортёр:
 HR GTV Croatia d o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska
 Distributor:
 ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón 308, 46021 Valencia, Spain
 CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince 879, 720 00 Ostrava Hrabová