


## PRODUCT INFORMATION SHEET

# Drill screwdriver 50Nm 18V + 2Ah battery







### Product description

Efficient device for drilling in wood, metal, as well as screwing in and unscrewing bolts, ensuring easy and speedy work. The 13 mm drill chuck and the torque of 50 Nm enable the possibility of using larger drill bits, making the tool more versatile in various applications. The two-speed gearbox and 21+1 settings of torque enable flexible adaptation of the power tool operation to the material and the task. Smooth adjustment of the rotational speed in the power switch provides full control over the conducted drilling and screwing operation. Changing the rotation of the power tool in both directions enable drilling, screwing in and unscrewing. The built-in, powerful LED illuminates the work areas perfectly. The additionally fixed handle for 6 bits organizes the equipment used. The robust, metallic self-locking chuck with the Auto-Lock safety feature, enables quick exchange of drills and bits with one hand. Durable, metallic housing of the gearbox excellently dissipates heat, making the device more efficient and robust. Gearbox made of metal enhances the wear resistance and ensures precision of the mechanism. Thermal safety device protects the tool against overheating during operation. Rubber bumpers protect the device against mechanical damage. Soft handle enables more reassuring hold of the power tool and dampens vibrations during operation. OneAccuSystem 18 V enables using the selected battery in a wide and diverse range of power tools for the most heavy-duty work.

### Characteristics

Soft torque – 25 Nm. Hard torque – 50 Nm. Torque adjustment steps – 21+1. Speed adjustment steps – 2. Drill chuck – Auto Lock, metal, 13 mm. Rotational speed: 0-450/0-1700 RPM. Maximum wood drilling diameter – 25 mm. Maximum steel drilling diameter – 13 mm. LED light. Bit holder. Smooth speed adjustment in the power switch. Soft handle. Right and left rotation direction switch. Metal gearbox housing. Metal gearbox mechanism. Device overheat protection. Weight – 1.3 kg. Sound pressure level – Lpa = 92 dB(A) Sound power level – Lwa = 103 dB(A) The rechargeable battery to be purchased separately. EAN code – 5902801441844. 3 years warranty after registering the tool. OneAccuSystem. Voltage – 18 V.

### Technical data

			
HT2E220-ODD-A20-PROMO	5902801602757	1	1

HögerT Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland

Producent/ Manufacturer/ Hersteller/ Произведено для:  
PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków, Polska/ Poland/ Polen/ Польша

Importer/ Импортёр:

HR GTV Croatia d.o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska

Distributor:

ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón 308, 46021 Valencia, Spain

CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince 879, 720 00 Ostrava Hrabová